

VitrA Fix P11



Powder tile cleaning material



DESCRIPTION

Acid-based powder which is used to remove cement and lime based mortar stains and residues (adhesives, grouting materials, plasters and etc.) from tile surfaces.

SURFACE PREPARATION

■ Prior to cleaning everything that might be affected from contact of acid either should be removed or safely covered allowing no air contact, such as marble and natural stone coverings, aluminum, inox or metal surfaces. ■ Prior to application the surface should be wetted with a sponge. ■ Ensure that substrate is sound and stable. ■ Avoid application on extremely hot or dry ambient conditions.

APPLICATION

■ VitrA Fix P11 is supplied as a powder. It should be scattered on the wetted surface. It is not necessary to cover the entire surface with powder. However, effect of the material should be pre-tested on a spare part of the cleaning surface prior to cleaning. ■ Wait for 5 minutes to let the powder affect and dissolve the stain and residue well. Then, rub all visible stains and residues with an abrasive sponge or brush, with care in order not to deform the tile surface. ■ After rubbing, clean the solution from the surface with a sponge or by using industrial vacuum cleaner. Do not let the solution to dry on the surface, and rinse the surface thoroughly with water several times. The surface, then, should be cleaned and polished with a clean and dry cloth in circular motion. ■ Due to hazardous effect of solution, ventilate the area and avoid splashes of product during application.

PRECAUTIONS

■ Application surface temperature must be above +0 °C. The surface should have no risk of freezing. ■ Material is not suitable for acid sensitive surfaces, inox, aluminum and metals, polished marbles or limestone and glazed tiles. It would cause fade-out and colour deterioration, corrosion and surface deformation. ■ A pre-test should be performed in a spare part of the surface to verify that the surface can be cleaned and is resistant to abrasion and acidic effect. ■ It should not contact with cementitious grouting materials for long. Contact may cause colour deteriorations and surface deformations in dark coloured grouts. ■ Vaporized solution has corrosive effect and this will cause chromium plating and metal parts and surfaces to corrode and fade. Prior to application, remove or cover all parts and surfaces that might be affected safely allowing no air contact.

STORAGE AND SHELF LIFE

■ When stored unopened in a cool, dry place at temperatures between 0 °C and 40 °C, shelf life is 12 months from date of manufacture. Production date and charge number is displayed on the packaging. ■ The products should not be stored in damped or submerged warehouses. Do not leave exposed to direct sunlight. ■ When not used, opened packages should be closed tightly to avoid air contact.

HEALTH AND SAFETY

S1/2: KEEP OUT OF THE REACH OF CHILDREN UNDER PROTECTIVE STORAGE. **R20/21:** Harmful by inhalation and skin contact. **R36/37/38:** Irritating to eyes, respiratory system and skin. **R42/43:** May cause sensitization by inhalation and by skin contact. **S24/S25:** Avoid contact with skin and eyes. **S26:** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **S28:** After contact with skin, wash immediately with plenty of water. **S38/39:** In case of insufficient ventilation, wear suitable respiratory equipment. **S45:** In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). **S46:** If swallowed, seek medical advice immediately and show the label informations.



Wash

Corrosive

Irritant / Do not breath

Attention

AREAS OF USE

Suitable for use on any format of tiles with acid resistant surfaces.

FEATURES

Type : Powder
Color : White
Density: 1,02 gr/cm³

APPLICATION PROPERTIES

Application temperature: +0 °C - +40 °C

COVERAGE

The approximate coverage amount (kg/m²) may vary depending on the format of stain or residue: 10-20 m²/kg.

PACKAGING

Plastic bottles of 1 kg (12 bottles / 12 kg in a box)

- Ideal for cleaning cement and lime based mortar stains after tiling,
- Easy to apply.



Note: The initial controls of our product are made during the production phase. We guarantee the stability of our products' quality. All recommendations and instructions on the technical sheet are generally based on our experience. Please contact us for applications on special surfaces not mentioned in the technical sheet. Our company reserves the right to update the information on the technical sheet in the case of technical necessities without prior notice. This new catalogue supercedes the previous editions.